



CHEVRON 1000 THF

PRODUCT DESCRIPTION

Chevron 1000 THF is a high quality, multifunctional tractor hydraulic fluid, specially formulated for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment employing a common fluid reservoir.

CUSTOMER BENEFITS

Chevron 1000 THF delivers value through:

- **Low operating costs** — Chevron 1000 THF meets or exceeds fluid performance requirements of most OEM's, maintaining efficiency and reliability while minimizing overall operating costs.
- **Long equipment life** — Special additives protect metal surfaces against scuffing and wear even under severe operating conditions leading to maximum equipment life.
- **Low inventory cost** — One fluid does the job of a full range of tractor hydraulic systems. Can replace multiple products and free up shelf space too!
- **Minimizing weather and storage concerns** — Protects against rust and corrosion of highly finished precision parts when operating in humid conditions and during seasonal shutdown periods.
- **Minimal downtime** — Good compatibility with seals, O-rings, and packing materials maintains their good condition and keeps leakage at a minimum.
- **Smooth operation** — Formulated to suppress brake "chatter" and transmission "slip" for quiet and efficient action of brakes and transmission.
- **Reliable operation** — Formulation helps keep metal parts clean and free of varnish and sludge deposits that could result in premature breakdown.
- **Fast service time** — Orange color helps identify origin point of incidental leaks for easy detection and quick remedy.

FEATURES

Chevron 1000 THF is a high quality, multifunctional tractor hydraulic fluid, specially formulated for use in transmissions, final drives, wet brakes, and hydraulic systems of tractors and other equipment employing a common fluid reservoir.

It is formulated with highly refined base stocks, a viscosity index improver, oxidation and corrosion inhibitors, antiwear and film strength additives, an antifoaming agent, and a pour point depressant.

Its distinctive orange color allows for easy product identification and leak detection.

Chevron 1000 THF meets the needs of modern tractors for a multi-functional lubricant. It is designed for many uses, such as lubrication of the transmission and final drive, and serves as a hydraulic fluid to operate power steering units, brakes, implements, and attachments.

Chevron 1000 THF is formulated to suppress brake "chatter" and excessive brake facing wear. It offers smooth operation of clutch packs and wet brakes, provides excellent shifting action, provides exceptional rust and corrosion protection for vital parts, and minimizes leakage because of good compatibility with seals, O-rings, and packing materials.

It helps prevent sludge and varnish formation, protects metal surfaces against scuffing and wear, and provides outstanding lubrication for spur, helical, and spiral bevel final drive gears.

Chevron 1000 THF is compatible with equipment manufacturer's proprietary fluids and other fluids of this type.

Product(s) manufactured in the USA, Colombia and El Salvador.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

24 September 2013

TTF-3

© 2008-2013 Chevron U.S.A. Inc. All rights reserved.

Chevron and the Chevron Hallmark are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

APPLICATIONS

Chevron 1000 THF is recommended for use:

- as a multifunctional fluid in many types of farm tractors and equipment.
- in non-hypoid GL-4 applications.
- in applications which call for the following OEM lubricant specifications:
 - **AGCO** — improved power fluid 821XL
 - **Case Corporation** — JIC-143, JIC-145, MS 1206, MS 1207, MS 1209, MS 1210 (TCH)
 - **Caterpillar** TO-2
 - **Ford New Holland** — ESN-M2C134-D, FNHA 2 C 201
 - **International Harvester** B6
 - **John Deere** — J20C
 - **Kubota** UDT
 - **Massey Ferguson** — M1135, M1141, M1143, M1145
 - **Minneapolis-Moline** — Q-1766, Q-1722, Q-1766B
 - **Oliver** — Q-1705
 - **Renk Doromat** — 874A and 874B
 - **Volvo** WB 101
 - **White Farm Equipment** — Q-1826

Chevron 1000 THF is also an excellent hydraulic fluid for many types of hydraulic systems requiring an anti-wear hydraulic fluid in this viscosity range. It passes the High Pressure Vane Pump Test, ASTM D2882, with less than 15 mg steel weight loss.

TYPICAL TEST DATA

<i>Product Number</i>	226606
<i>MSDS Number</i>	
USA	7648
Colombia	33702
El Salvador	33703
API Gravity	29.9
Viscosity, Kinematic	
cSt at 40°C	58.4
cSt at 100°C	9.5
Viscosity, Saybolt	
SUS at 100°F	298
SUS at 210°F	58.3
Viscosity, Brookfield	
cP at -35°C	40,000
Viscosity Index	145
Flash Point, °C(°F)	235(455)
Pour Point, °C(°F)	-42(-44)
Color	Orange

Minor variations in product typical test data are to be expected in normal manufacturing.

Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.