



# CHEVRON SYNTHETIC TURBINE OIL SGT

## PRODUCT DESCRIPTION

Chevron Synthetic Turbine Oil SGT is designed for use in modified aviation-type gas turbines in non-aviation stationary applications such as in industrial power generation and in marine service.

## CUSTOMER BENEFITS

Chevron Synthetic Turbine Oil SGT delivers value through:

- **Long service life** — Excellent oxidation and thermal stability of the synthetic polyol ester base fluid and special additive system helps resist oil breakdown under severe, high temperature, high load conditions. The low volatility of the synthetic ester helps minimize evaporative losses.
- **Minimal maintenance and downtime** — Minimal coking tendency of the synthetic ester base fluid and additive system helps minimize deposit formation on bearings and other areas exposed to the heat of the hot gases. High load carrying capacity helps ensure excellent protection against wear. The oil is compatible with normal engine and accessory metallic construction materials and elastomeric sealing compounds.
- **Excellent all-temperature performance** — Excellent viscosity-temperature characteristics of the synthetic ester help promote outstanding low temperature fluidity to facilitate starting at low temperatures, while helping to ensure that an effective lubricant film is always available under the most severe, high temperature conditions to protect critical components against wear.

## FEATURES

Chevron Synthetic Turbine Oil SGT is a premium performance, synthetic polyol ester-based turbine lubricant for use in modified aviation-type gas turbines in stationary and marine service. A special additive system imparts excellent high temperature thermal and oxidation stability.

Product(s) manufactured in Europe.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

8 July 2011  
IO-220

© 2007-2011 Chevron U.S.A. Inc. All rights reserved.

Chevron and the Chevron Hallmark are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

## APPLICATIONS

Chevron Synthetic Turbine Oil SGT has well over 2.5 million fired hours with excellent performance. It is designed for modified aviation-type gas turbines exposed to the most severe operating environment in non-aviation applications such as industrial power generation and marine propulsion.



Chevron Synthetic Turbine Oil SGT is approved for:

- U.S. Military Specification **MIL-PRF-23699F, Class STD**
- **Rolls Royce** Model RB 211
- **Rolls Royce (Allison)** 501 models

Chevron Synthetic Turbine Oil SGT meets the requirements of:

- **General Electric** (D50 TF-1) LM 500, 1600, 2500, 5000 and 6000 models
- **Rolls Royce** Avon, Olympus, Tyne, and Spey models
- **Turbomeca Makila**

Chevron Synthetic Turbine Oil SGT is compatible with other lubricants approved under MIL-PRF-23699F. Chevron Synthetic Turbine Oil SGT is compatible with metals, paints, coatings and elastomers such as Viton, Teflon, fluorosilicone and Buna N (NBR).

Chevron Synthetic Turbine Oil SGT is not to be used in aircraft service. Chevron Synthetic Turbine Oil SGT is not recommended for gas turbines that require MIL-PRF-23699F, Class C/I (Corrosion Inhibiting) or HTS (High Thermal Stability).

**TYPICAL TEST DATA**

<i>Product Number</i>	253100
<i>MSDS Number</i>	12310
Viscosity, Kinematic cSt at -40° C cSt at 40° C cSt at 100° C	9,800 25.6 5.13
Operating Temperature °C(°F) Minimum Maximum	-40(-40) 204(400)
Flash Point, °C(°F)	270 (518)
Pour Point, °C(°F)	-60(-76)
Acid number, mg KOH/g	0.16

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.